





## Interfacing M-series PLCs To TAIAN OP16/OP26L/OP36 HMI

<p><b>1. Controller/PLC Type</b></p> <p>Choose Modicon 984 RTU as the PLC type.</p>													
<p><b>2. Communication Parameters.</b></p> <p>Set to PLC's default of 38400 bps, 8 data bits, no parity and 1 stop bit. It is assumed that the PLC is defined with ID = 01 (factory default).</p>													
<p><b>3. I/O Bit Mappings</b></p>	<table> <thead> <tr> <th>I/O Type</th><th>MODBUS PLC Bit Addr</th></tr> </thead> <tbody> <tr> <td>Inputs 1–256</td><td>1 – 256</td></tr> <tr> <td>Outputs 1–256</td><td>257 – 512</td></tr> <tr> <td>Timers 1–64</td><td>513 – 576</td></tr> <tr> <td>Counters 1–64</td><td>769 – 833</td></tr> <tr> <td>Relays 1-512</td><td>1025-1536</td></tr> </tbody> </table>	I/O Type	MODBUS PLC Bit Addr	Inputs 1–256	1 – 256	Outputs 1–256	257 – 512	Timers 1–64	513 – 576	Counters 1–64	769 – 833	Relays 1-512	1025-1536
I/O Type	MODBUS PLC Bit Addr												
Inputs 1–256	1 – 256												
Outputs 1–256	257 – 512												
Timers 1–64	513 – 576												
Counters 1–64	769 – 833												
Relays 1-512	1025-1536												
<p><b>4. I/O Channel Mappings</b></p>	<table> <thead> <tr> <th>I/O Variable</th><th>MODBUS PLC Word Addr</th></tr> </thead> <tbody> <tr> <td>Input[1] – [16]</td><td>40001 - 40016</td></tr> <tr> <td>Output[1] – [16]</td><td>40017 – 40032</td></tr> <tr> <td>Timer[1] –[4]</td><td>40033 – 40036</td></tr> <tr> <td>Counters [1]–[64]</td><td>40049 – 40052</td></tr> <tr> <td>Relay[1] – [32]</td><td>40065 - 40096</td></tr> </tbody> </table>	I/O Variable	MODBUS PLC Word Addr	Input[1] – [16]	40001 - 40016	Output[1] – [16]	40017 – 40032	Timer[1] –[4]	40033 – 40036	Counters [1]–[64]	40049 – 40052	Relay[1] – [32]	40065 - 40096
I/O Variable	MODBUS PLC Word Addr												
Input[1] – [16]	40001 - 40016												
Output[1] – [16]	40017 – 40032												
Timer[1] –[4]	40033 – 40036												
Counters [1]–[64]	40049 – 40052												
Relay[1] – [32]	40065 - 40096												

<b>5. Other Variable Mappings</b>	<table border="1"> <thead> <tr> <th>I/O Variable</th><th>MODBUS PLC Word Addr</th></tr> </thead> <tbody> <tr> <td>TimerPV[1]–[64]</td><td>40129 – 40192</td></tr> <tr> <td>CtrPV[1]–[64]</td><td>40257 – 40320</td></tr> <tr> <td>TIME[1] – [3]</td><td>40513 – 40515</td></tr> <tr> <td>DATE[1] –[4]</td><td>40517 – 40520</td></tr> </tbody> </table>	I/O Variable	MODBUS PLC Word Addr	TimerPV[1]–[64]	40129 – 40192	CtrPV[1]–[64]	40257 – 40320	TIME[1] – [3]	40513 – 40515	DATE[1] –[4]	40517 – 40520
I/O Variable	MODBUS PLC Word Addr										
TimerPV[1]–[64]	40129 – 40192										
CtrPV[1]–[64]	40257 – 40320										
TIME[1] – [3]	40513 – 40515										
DATE[1] –[4]	40517 – 40520										
<b>6. Data Memory Mappings</b>	<table border="1"> <tbody> <tr> <td>DM[1]-DM[4000]</td><td>41001 – 45000</td></tr> <tr> <td>E.g. DM[3991]</td><td>3991+41000 = 44991</td></tr> </tbody> </table>	DM[1]-DM[4000]	41001 – 45000	E.g. DM[3991]	3991+41000 = 44991						
DM[1]-DM[4000]	41001 – 45000										
E.g. DM[3991]	3991+41000 = 44991										
<b>7. Communication Cable:</b> <p>The Taian OP16/26/36 models of HMI may be connected to either the RS485 port or the RS232 port of the T100MD+ PLCs. We present here both methods of wiring the HMI to the PLCs.</p> <p>However, we recommend using the RS485 port for connecting the HMI since it leaves the RS232 port free for programming and on-line monitoring.</p> <p><b>Note:</b> If using RS232 port for T100MX+ PLC, you need to connect an external +9V power to pin 4 of the DB9 plug to power the opto-isolated interface. T100MD+ PLC do not require connection to pin 4.</p>	<p><b>(a) RS485 (recommended)</b></p>  <p><b>(b) RS232</b></p> 										
<b>8. HMI's DIP Switch Setting</b>	<p>ON: DIP Switch 1,2,3,4,7,8,9,10</p> <p>OFF: DIP Switch 5,6</p>										
<b>9. Example HMI Definition</b> <b>File: T100MD.P3F</b> Monitor: Input 1,6; Relay 4. Push button: Output 1,5. Numeric entry: DM[5] Numeric display and panel meter: TIME[3]	